

Tekniset tiedot

- Koko	47 x 29 x 12 mm (GT-100) 44,5 x 28,5 x 13 mm (GT-120)
- Paino	21g (GT-100) 20g (GT-120)
- GPS-piirisarja	SiRF StarIII low-power
- GPS-antenni	Keraaminen patch
- Akku	230mAh Lithium-ion
- Muisti	Flash muisti, 16000 reittipistettä (GT-100) Flash muisti, 65000 reittipistettä (GT-120)
- LED	Punainen ja sininen (lataus ja GPS)
- GPS-haku aika	< 60 s cold start, < 38 s warm start (GT-100) < 35 s cold start (GT-120)
- PC-yhteys	USB1.1 tai USB2.0
- Käyttölämpötila	-10deg - +50deg
- Tekninen tuki	support@traxmeet.com
- PC-vaatimukset	Win2000, XP, Vista, USB1.1 tai USB2.0
- Vesitiiviys	Roiskevesitiivis (IPX-6)



Manuf. Elisa Oyj
www.elisa.com

© Elisa Oyj
www.mylogger.net
Made in Taiwan

Technical Specification

- Dimensions	47 x 29 x 12 mm (GT-100) 44,5 x 28,5 x 13 mm (GT-120)
- Weight	21g (GT-100) 20g (GT-120)
- GPS chipset	SiRF StarIII low-power
- GPS antenna	Ceramic patch
- Battery	230mAh Lithium-ion
- Memory	Flash memory, 16000 waypoints (GT-100) Flash memory, 65000 waypoints (GT-120)
- LED	Red and blue (charging and GPS)
- GPS acquisition time	< 60 s cold start, < 38 s warm start (GT-100) < 35 s cold start (GT-120)
- PC-connection	USB1.1 or USB2.0
- Operation temperature	-10deg - +50deg
- Technical support	support@traxmeet.com
- PC requirements	Win2000, XP, Vista, USB1.1 or USB2.0
- Water resistance	Splash proof hardware design (IPX-6)